

Date	2006/12/08
Revision	A



TECHNICAL DATA				TOLERANCE	
HOUSING	PC+ABS UL94V-0			.XXXX	---
CONTACT	0.46 DIAMETER PHOSPHOR BRONZE GOLD PLATED OVER NICKEL			.XXX	0.10
GOLD-PLATING	☐ 0.0762 um / 3u inch ☐ 0.15 um / 6u inch ☐ 0.38 um / 15u inch			.XX	0.25
	☐ 0.76 um / 30u inch ☒ 1.27 um / 50u inch			.X	0.38
COLOR	☐ RED ☐ BLACK ☒ WHITE ☐ BLUE ☐ OTHER _____			---	0.50
	UL Applications Max. 250VAC/2Amp Dielectrical with Standing Voltage			500VAC	
Insulation Resistance	Min. 500M Ω Termination Resistance (After Environmental Test)			Max. 35m Ω	
REV.	DESCRIPTION			ENG.	APPROVAL



NEX1 Technologies Co., Ltd
 TEL: (02) 2518-1500
 FAX: (02) 2501-4209

P/NO. NKSJ-TL-C6

ITEM Keystone Jack		CO. SY
DR. Hansum2006/12/08		APPD.
FILE SY-504E		S/N.NKSJ-TL-C6
SCALE /		CHKD.
UNIT mm	SIZE A4	

